

KENZOIL HYDRAULIC OIL AW

GRADES AVAILABLE - KENZOIL HYDRAULIC OIL AW 32, 46, 68, 100, 150, 220, 320, & 460

APPLICATION

- ☞ Kenzoil Hydraulic AW oils are recommended for hydraulic system, circulation system of industrial Gearboxes, air compressors requiring turbine quality oil and for plain and anti-friction bearings of turbo Feed pumps, turbo blowers, etc.

DESCRIPTION

- ☞ Kenzoil Hydraulic AW oil range is a group of premium quality, transparent and antiwear hydraulic oils. They are blended from high viscosity index base oils with selected antiwear and other additives. These oils are designed to operate a wide range of working conditions including low load and high load conditions.

PERFORMANCE BENEFITS

Kenzoil Hydraulic AW oil

- ☞ High viscosity index combined with low pour point.
- ☞ Excellent wear protection at high temperatures and severe operating conditions.
- ☞ Superior anti-wear properties and equipment protection.
- ☞ Enhanced Hydraulic life.

SAE GRADE	Method	ISO VG 32	ISO VG 46	ISO VG 68	ISO VG 100	ISO VG 150	ISO VG 220	ISO VG 320	ISO VG 460
Appearance		Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear
Density @15°C, gm/ml	ASTM D-1298	0.830	0.846	0.866	0.876	0.880	0.880	0.886	0.886
Viscosity @40°C, cSt	ASTM D-445	29 - 35	42 - 50	62 - 70	95 - 105	135 - 165	215 - 225	310 - 335	430 - 480
Viscosity Index	ASTM D-2270	95	95	95	90	90	90	90	90
Flash point, COC, °C	ASTM D-92	195	200	210	210	230	230	230	250

Packaging Options :- kenzoil is offered in 20, 26, 50, & 210 Liters.