

KENZOIL THERMIC OIL

GRADES AVAILABLE - KENZOIL THERMIC OIL MEDIUM & SUPER

APPLICATION

- ☞ Kenzoil Thermic oil All types of heat transfer applications. This grades application in textile, pharmaceuticals, chemical and processing industries.

DESCRIPTION

- ☞ Kenzoil thermic oils have been specially developed for use as heat transfer industrial application. These oils possess high viscosity index, excellent thermal and oxidation stability, low volatility and low vapour pressure to give long service life in well designed heat transfer systems.

PERFORMANCE BENEFITS

- ☞ Excellent heat transfer properties.
- ☞ Excellent chemical & oxidation stability
- ☞ Superior anti-wear properties and equipment protection.

SAE GRADE	Method	MEDIUM	SUPER
Appearance	Visual	Bright & Clear	Bright & Clear
Density @ 29.5, *C, gm/ml	ASTM D-1298	0.820	0.820
Viscosity @40°C, cSt	ASTM D-445	29 - 35	28 - 35
Viscosity Index	ASTM D-2270	90	95
Flash point, COC, °C Min	ASTM D-92	208	215

Packaging Options :- kenzoil is offered in 20, 26, 50, & 210 Liters.

HEALTH & SAFETY :- These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.