

KENZOIL AUTOMOTIVE & INDUSTRIAL GEAR OILS

GRADES AVAILABLE - KENZOIL AUTOMOTIVE & INDUSTRIAL GEAR OILS 85W-140, 80W-90, 140, 90

APPLICATION

Kenzoil Automotive & Industrial Gear Oils are recommended for.

☞ Kenzoil 85W-140/80W-90/HP 140/HP 90 is recommended for all types of gear boxes and hypoid gears under extreme duty conditions. Suitable for earth moving equipment and passenger cars. Heavy duty manual transmissions, axles, heavy-duty trucks, light vehicles and industries such as construction, mining and agriculture.

DESCRIPTION

☞ Kenzoil Gear oils are an extreme pressure hypoid gear oil. This oil is blended from selected base stocks and contain specific additive package to provide extreme pressure, anti wear characteristics.

PERFORMANCE BENEFITS

Kenzoil Gear Oils

- ☞ Satisfy the lubrication requirements of a wide range of gears.
- ☞ Enhanced Gear life.
- ☞ Good stability at high temperatures.

SAE GRADE	Method	85W-140	80W-90	HP 140	HP 90
Appearance		Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear
Density @15°C, gm/ml	ASTM D-1298	0.89	0.88	0.89	0.88
Viscosity @100°C, cSt	ASTM D-445	28 - 34	14 - 16	28 - 34	16 - 18
Viscosity Index	ASTM D-2270	90	90	90	90
Pour Point, °C Max.	ASTM D-97	(-) 12	(-) 24	(-) 6	(-) 9
Flash point, COC, °C	ASTM D-92	210 Min	210 Min	220 Min	210 Min

Packaging Options :- kenzoil is offered in (Hp 140 / 90) 1 , 5 , 20 , 26 , 50 & 210 Liters.
(85W-140 / 80W-90) 26 , 50 & 210 Liters.

HEALTH & SAFETY :- These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.