

KENZOIL REFRIGERATION OIL

GRADES AVAILABLE - KENZOIL REFRIGERATION OIL 32, 46 & 68

APPLICATION

- Kenzoil Refrigeration oil are blended using highly quality oil, specially treated straight mineral oils designed for very low temperature applications. Kenzoil are recommended for a wide range of refrigeration compressors using all conventional Refrigerants.

DESCRIPTION

- Kenzoil Refrigeration oil range is a premium quality, They are blended from high viscosity index base oils with Selected antiwear and other additives. These oils are designed to operate a wide range of working conditions including low load and high load conditions. Kenzoil refrigeration oil are recommended for a wide range of refrigeration compressors using all conventional refrigerants.

PERFORMANCE BENEFITS

- High viscosity index combined with low pour point.
- Excellent wear protection at high temperatures and severe operating conditions.
- Superior anti-wear properties and equipment protection.

SAE GRADE	Method	ISO VG 32	ISO VG 46	ISO VG 68
Appearance		Bright & Clear	Bright & Clear	Bright & Clear
Density @ 29.5, *C, gm/ml	ASTM D-1298	0.825	0.830	0.840
Viscosity @40°C, cSt	ASTM D-445	29 - 35	42 - 50	62 - 70
Viscosity Index	ASTM D-2270	95	95	95
Flash point, COC, °C Min	ASTM D-92	195	195	200

Packaging Options :- kenzoil is offered in 20, 26, 50, & 210 Liters.

HEALTH & SAFETY :- These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.