

KENZOIL SPINDLE OILS

GRADES AVAILABLE - KENZOIL SPINDLE OILS 10, 12 & 22

APPLICATION

- ☞ Kenzoil spin oils are recommended for bearing lubrication of high speed textile spindles machine. high quality spindle lubricants for use on modern textile machines.

DESCRIPTION

- ☞ Kenzoil Spin oil range is a premium quality, transparent and antiwear spindle oils. They are blended from high viscosity index base oils with selected antiwear and other additives. These oils are designed to operate a wide range of working conditions including low load and high load conditions. Spin oil use on ultramodern textile machines.

PERFORMANCE BENEFITS

- ☞ High viscosity index combined with low pour point.
- ☞ Excellent wear protection at high temperatures and severe operating conditions.
- ☞ Superior anti-wear properties and equipment protection.
- ☞ Enhanced looms machin life.

SAE GRADE	Method	10	12	22
Appearance	Visual	Bright & Clear	Bright & Clear	Bright & Clear
Density @ 29.5 *C, g/ml	ASTM D 1298	0.81	0.82	0.82
Viscosity @40°C, cSt	ASTM D-445	9 - 12	10 - 14	20 - 24
Flash point, COC, °C	ASTM D-92	170	170	180

Packaging Options :- kenzoil is offered in 20, 26, 50, & 210 Liters.

HEALTH & SAFETY :- These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.