

KENZOIL INDUSTRIAL GEAR OIL

GRADES AVAILABLE - KENZOIL INDUSTRIAL GEAR OIL 32, 46, 68, 100, 150, 220, 320, 460, & 680

APPLICATION

- ☞ Kenzoil Gear oil high load carrying capacity and anti-friction property offer excellent performance in industrial Gears and other industrial applications. Recommended for use in all type of gear box etc...

DESCRIPTION

- ☞ Kenzoil oils are premium quality industrial gear lubricants. Gear Oils are produced with high quality base oils blended with EP, antioxidant, anti-corrosion and anti-wear additives. Gear oil high load carrying capacity and anti-friction property offer excellent performance in industrial gears and other industrial applications.

PERFORMANCE BENEFITS

- ☞ Excellent stability at high temperatures.
- ☞ Excellent wear protection at high temperatures and severe operating conditions.
- ☞ Superior anti-wear properties and equipment protection.
- ☞ Enhanced Gear life.

SAE GRADE	Method	ISO VG 32	ISO VG 46	ISO VG 68	ISO VG 100	ISO VG 150	ISO VG 220	ISO VG 320	ISO VG 460
Colour, max	ASTM D 1500	2.5	2.5	3.5	3.5	4.0	4.0	5.0	5.0
Appearance		Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear
Density @29.5°C, gm/ml	ASTM D-1298	0.830	0.846	0.860	0.870	0.875	0.880	0.886	0.886
Viscosity @40°C, cSt	ASTM D-445	29 - 32	44 - 50	62 - 70	95 - 105	145 - 165	215 - 225	310 - 335	430 - 480
Viscosity Index	ASTM D-2270	90	90	90	90	90	90	90	90
Flash point, COC, °C	ASTM D-92	195	200	210	210	230	230	230	250

Packaging Options :- kenzoil is offered in 20, 26, 50, & 210 Liters.

 **Office** : 8, J. M. Complex, Near Lupin Ltd. GIDC, Ankleshwar 393002, Gujarat, India

Factory : Plot No. 905/11/14, GIDC, Panoli 394116, Gujarat, India

 Customer Care: 9909986900

 patelmilan_vsa@yahoo.com

 www.kenzoilubes.com